1 **EU - TYPE EXAMINATION CERTIFICATE**

- 2 Equipment or Protective System Intended for use in Potentially Explosive Atmospheres Directive 2014/34/EU
- Baseefa04ATEX0384 Issue 16 3 EU - Type Examination Certificate Number:
- 3.1 In accordance with Article 41 of Directive 2014/34/EU, EC-Type Examination Certificates referring to 94/9/EC that were in existence prior to the date of application of 2014/34/EU (20 April 2016) may be referenced as if they were issued in accordance with Directive 2014/34/EU. Supplementary Certificates to such EC-Type Examination Certificates, and new issues of such certificates, may continue to bear the original certificate number issued prior to 20 April 2016.

Product: Gasman Oxygen or Toxic Gas Detector

5 Manufacturer: **Crowcon Detection Instruments Ltd**

172 Brook Drive, Milton Park, Abingdon, Oxfordshire OX14 4SD 6 Address:

- 7 This re-issued certificate extends EC Type Examination Certificate No. Baseefa04ATEX0384 to apply to product designed and constructed in accordance with the specification set out in the Schedule of the said certificate but having any variations specified in the Schedule attached to this certificate and the documents therein referred to.
- SGS Baseefa, Notified Body number 1180, in accordance with Article 17 of Directive 2014/34/EU of the European Parliament 8 and of the Council, dated 26 February 2014, certifies that this product has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of products intended for use in potentially explosive atmospheres given in Annex II to the Directive.

The examination and test results are recorded in confidential Report No. See Certificate History

9 Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

EN 60079-0: 2012 + A11: 2013 EN 60079-11: 2012

except in respect of those requirements listed at item 18 of the Schedule.

- 10 If the sign "X" is placed after the certificate number, it indicates that the product is subject to the Specific Conditions of Use specified in the schedule to this certificate.
- This EU TYPE EXAMINATION CERTIFICATE relates only to the design and construction of the specified product. Further 11 requirements of the Directive apply to the manufacturing process and supply of this product. These are not covered by this
- 12 The marking of the product shall include the following:

(a) II 1 G Ex ia IIC T4 Ga (-20° C $\leq T_a \leq +65^{\circ}$ C)

SGS Baseefa Customer Reference No. 0249

Project File No. 19/0718

This document is issued by the Company subject to its General Conditions for Certification Services accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and the Supplementary Terms and Conditions accessible at http://www.sgs.com/SGSBaseefa/Terms-and-Conditions.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. It does not necessarily indicate that the equipment may be used in particular industries or circumstances. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, schedule included, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Baseefa Limited

Rockhead Business Park, Staden Lane, Buxton, Derbyshire SK17 9RZ Telephone +44 (0) 1298 766600 Fax +44 (0) 1298 766601 e-mail baseefa@sgs.com web site www.sgs.co.uk/baseefa

Registered in England No. 4305578.

Registered address: Rossmore Business Park, Ellesmere Port, Cheshire, CH65 3EN

R S SINCLAIR TECHNICAL MANAGER On behalf of SGS Baseefa Limited



Issued 10 August 2020 Page 2 of 6

13 Schedule

Certificate Number Baseefa04ATEX0384 – Issue 16

15 Description of Product

14

The Gasman Oxygen or Toxic Gas Detector is designed to detect the presence of oxygen (deficiency) or toxic gas, give a visual indication of the concentration, and give audible and visual alarms if a preset level is exceeded. It comprises a battery, a gas sensor head, electronic circuits on printed circuit boards, a liquid crystal display, LED's and a piezo sounder, all contained in a plastic enclosure providing a degree of protection of at least IP20. Two types are available, one rechargeable, and one non-rechargeable. External contacts are provided for recharging, and for serial data communications.

The sensors are known as Oxygen or Toxic i-modules, and the permitted modules are listed in the User Manual provided by the manufacturer.

The apparatus is not designed for use in oxygen enriched atmospheres.

The cell in the non-chargeable apparatus must only in changed when in a non-hazardous area, and replaced only with cell type CR2.

Charging conditions:

The apparatus must only be recharged or connected to serial communications when in a non-hazardous area, using the following chargers: -

Crowcon desktop charger / interface part number C01940

Crowcon desktop charger part number C01941

Crowcon desktop charger / Bluetooth Interface part number C011023

Alternatively, any Crowcon charger with an output (U_m) of 9V may be used to charge the apparatus, although when both charging and data communications are required, only charger / interface part number's C01940 & C011023 must be used.

16 Report Number

See Certificate History

17 Specific Conditions of Use

None

18 Essential Health and Safety Requirements

In addition to the Essential Health and Safety Requirements (EHSRs) covered by the standards listed at item 9, the following are considered relevant to this product, and conformity is demonstrated in the report:

| Clause | Subject |
|--------|--|
| 1.2.7 | LVD type requirements |
| 1.2.8 | Overloading of equipment (protection relays, etc.) |
| 1.4.1 | External effects |
| 1.4.2 | Aggressive substances, etc. |

19 Drawings and Documents

New drawings submitted for this issue of certificate:

| Number | Sheet | Issue | Date | Description |
|-----------|--------|-------|------------|-----------------------------------|
| P-5460 | 1 of 1 | 06 | 2020-07-14 | Gasman Charger/Interface Assembly |
| P-5495-A4 | 1 of 1 | 6 | 07/20 | Gasman Charger Label |



Issued 10 August 2020 Page 3 of 6

| Number | Sheet | Issue | Date | Description |
|--------------------------|--------|-------|------------|---|
| ECAD-000212-CD- CERT | 1 of 1 | 1 | 30/06/2020 | T3 & Gasman Bluetooth Dock Board (Circuit Diagram) |
| ECAD-000212-PCB- CERT | 1 to 6 | 1 | 03/07/2020 | T3 & Gasman Bluetooth Charger Board (PCB & Track Layout) |
| ECAD-000212-PL-CERT | 1 of 1 | 1 | 30/06/2020 | T3 & Gasman Bluetooth Dock Board (Safety Critical Parts List) |

The above drawings are associated and held with IECEx Certificate No. IECEx BAS 05.0039 Iss. 16

Current drawings which remain unaffected by this issue:

| Number | Sheet | Issue | Date | Description |
|----------------|--------|-------|------------|---|
| MCAD-000344 | 1 of 1 | 03 | 16/11/2011 | Gasman Battery |
| MCAD-003518 | 1 of 1 | 01 | 24/04/2018 | Front Case Assembly |
| MCAD-003519 | 1 of 1 | 01 | 24/04/2018 | Rear Case Assembly |
| 5430-CERT | 1 of 1 | 7 | 10/09 | Gasman Instrument G A - Rechargeable |
| 5423-CD-CERT | 1 of 1 | 6 | 27/10/09 | Gasman Rechargeable – Main PCB (Circuit Diagram) |
| P-5424-A2 | 1 of 1 | 2 | 08/05 | Main Board Rechargeable PCB & Track Details |
| 5425-PL | 1 & 2 | 4 | 27/10/09 | Gasman Rechargeable Main Board Certification Parts List |
| P-5456-A4 | 1 of 1 | 5 | 08/09 | Toxic / Oxygen Gasman Serial / Model No Label |
| P-5517 Issue 3 | 1 of 1 | 3 | 01/06 | Hybrid 1A (Circuit Diagram) |
| P-5406-A3 | 1 of 1 | 4 | 07/06 | Gasman Type 1A Hybrid Mech and Tracking Details |
| 5407-CERT | 1 of 1 | 7 | 10/07 | Crowcon Type 1A ("Rechargeable") Hybrid Certification Parts List |
| P-5516 Issue 4 | 1 of 1 | 4 | 08/09 | Hybrid 1B (Circuit Diagram) |
| 5411-CERT | 1 of 1 | 6 | 10/07 | Crowcon Type 1B ("Encapsulated Fuse") Hybrid Certification Parts List |
| P-5410-A3 | 1 of 1 | 3 | 07/06 | Gasman Type 1B Hybrid Mech and Tracking Details |
| 5567-CD-CERT | 1 of 1 | 1 | 29/10/09 | Hybrid 3 (Circuit Diagram) |
| 5567-PCB-CERT | 1 of 1 | 1 | 29/10/09 | Hybrid 3 PCB Drawing |
| 5567-PL-CERT | 1 of 1 | 1 | 28/10/09 | Crowcon Type 3 Hybrid Certification Parts List |
| 5553-CERT | 1 of 1 | 1 | 05/08 | Gasman Certification Instrument Names |
| P-5472-A2 | 1 of 1 | 3 | 08/09 | Gasman Instrument G A – Non Rechargeable |
| P5401 Issue 6 | 1 of 1 | 6 | 10/8/06 | Gasman (Budgie) non-rechargeable (Schematic) |
| P-5402-4A | 1 of 1 | 4 | 05/06 | Gasman (2005) Non-rechargeable Main PCB Details |
| P-5403-A4 | 1 of 1 | 5 | Sept 2006 | Gasman Non Rechargeable Main Board Certification Parts List |
| P-5499-A4 | 1 of 1 | 2 | 06/05 | Gasman Conformal Coating of Non-rechargeable Main PCB |
| P5506 issue 2 | 1 of 1 | 2 | 13/9/06 | Gasman Type 2 Hybrid (Circuit Diagram) |
| P-5414-A3 | 1 of 1 | 4 | 01/07 | Gasman Type 2 Non-rechargeable Hybrid Mech and Tracking Details |
| 5415-CERT | 1 of 1 | 5 | 10/07 | Crowcon Type 2 ("Non Rechargeable") Hybrid Certification Parts List |
| 5490-CD-CERT | 1 of 1 | 4 | 16-11-2012 | i-module oxygen |
| P-5476-A3 | 1 of 1 | 2 | 06/05 | Oxygen i-Module PCB & Track Details (used only for general physical size of module) |



Issued 10 August 2020 Page 4 of 6

| Number | Sheet | Issue | Date | Description |
|-------------------------|--------|-------|-----------|--|
| 5494-PL-CERT | 1 & 2 | 7 | 18/09/17 | Oxygen I-Module Certification Parts List |
| P-5488 Issue 3 | 1 of 1 | 3 | 13/9/06 | Tetra / Gasman Toxic iModule (Circuit Diagram) |
| P-5477-A3 | 1 of 1 | 2 | 06/05 | Toxic i-Module PCB & Track Details (used only for general physical size of module) |
| 5493-PL-CERT | 1 & 2 | 9 | 12/09/17 | Toxic I-Module Certification Parts List |
| P-5518 issue 3 | 1 of 1 | 3 | 22/09/06 | Tetra/Gasman COSH iModule (Circuit Diagram) |
| P-5526-A3 | 1 of 1 | 1 | 10/05 | COSH i-Module PCB & Track Details (used only for general physical size of module) |
| P-5520 Issue 1 | 1 of 1 | 1 | 6/9/05 | Alphasense COSH iModule Adapter |
| P-5527-A3 | 1 of 1 | 1 | 10/05 | Alphasense D2 COSH i-Module Adapter PCB & Track Details |
| 5844-PL-CERT | 1 & 2 | 4 | 12/09/17 | Dual Toxic i-Module Certification Parts List |
| P-5427 issue 5 Charger | 1 of 1 | 5 | 12/3/07 | Gasman Charger (Circuit Diagram) |
| P-5428 | 1 to 6 | 4 | 11/1/07 | Gasman (Budgie) Charger PCB |
| P5437 issue 1 Interface | 1 of 2 | 1 | 20/12/04 | Gasman Interface PCB (Circuit Diagram) |
| P-5438-A3 | 1 of 1 | 1 | 02/05 | Gasman Interface PCB and Track Details |
| P-5429-A4 | 1 of 1 | 3,4,5 | 12.3.2007 | Gasman External Charger Certification Parts List |
| P-5439-A4 | 1 of 1 | 1 | 3.3.2005 | Gasman External Interface Certification Parts List |

The above drawing are associated and held with IECEx Certificate No. IECEx BAS 05.0039

20 Certificate History

| Certificate No. | Date | Comments |
|---------------------|------------------|--|
| Baseefa04ATEX0384 | 10 May 2005 | The release of the prime certificate. The associated test and assessment against the requirements of EN 50014: 1997 + Amd. 1 & 2 & EN 50020: 2002 is documented in Test Report No. 04(C)0202. |
| Baseefa04ATEX0384/1 | 22 June 2005 | 1. To permit the use of an alternative rechargeable battery on the rechargeable versions of the apparatus. |
| | | 2. To permit changes to the general assembly and main PCB to incorporate a ½AA size cell on the non-rechargeable version. Also to permit the use of the following type C2R cells: Panasonic Power Lithium, GP Photo Lithium, Maxell Photo-Power Lithium, or Energizer Photo Lithium. |
| | | 3. To permit minor changes to the oxygen and toxic i-modules and other minor drawing changes not affecting the original assessment on all models of the apparatus. |
| | | The changes are documented in Test Report No. 05(C)0256. |
| Baseefa04ATEX0384/2 | 10 February 2006 | To permit the optional use of an alternative sensor module known as dual toxic and other minor drawing changes not affect the original assessment as documented in Test Report No. 05(C)0256/1. |
| Baseefa04ATEX0384/3 | 11 April 2006 | To permit a change of encapsulant in the hybrid circuits. |
| Baseefa04ATEX0384/4 | 12 July 2006 | To permit the use of alternative model names Gas-Mate, Oxy-Mate CR and Toxi-Mate CR and minor additions to the Oxygen and Toxic i-Module Certification Parts Lists, and a minor change to Hybrid 1A. |



Issued 10 August 2020 Page 5 of 6

| Certificate No. | Date | Comments |
|-------------------------------|-------------------|---|
| Baseefa04ATEX0384/5 | 15 September 2006 | To permit minor drawing changes, the use of alternative sounders, and the use of an alternative CO2 chemical i-module as documented in Test Report No. 06(C)0673. |
| Baseefa04ATEX0384/6 | 8 December 2006 | To permit minor changes to the desktop charger units with part number C01940 and C01941. Also to permit the replacement of desktop charger C01941 with any Crowcon charger with an output (U_m) of 9V. When both charging and data communication are required, only charger / interface part number C01940 must be used as documented in Test Report No. 06(C)1022. |
| Baseefa04ATEX0384/7 | 4 July 2007 | To permit minor changes to drawings and minor modification to circuits. |
| Baseefa04ATEX0384/8 | 4 April 2008 | To permit the use of an alternative cell type ICP653450U. When this cell is used, the marking becomes: |
| | | \textcircled{E} II 1G Ex ia IIC 170°C (T3) (-20°C \leq T _a \leq +65°C) |
| | | Testing documented in Test Report No. 08(C)0211 |
| Baseefa04ATEX0384/9 | 12 June 2008 | To permit use of an alternative encapsulant in the hybrids, the use of an alternative model name Gasalarm and the introduction of a new drawing listing the possible model names. |
| Baseefa04ATEX0384/10 | 6 August 2008 | To permit the use of an alternative rechargeable cell Sanyo Type UF553450Z. When this cell is used the marking is: |
| | | \textcircled{E} II 1G Ex ia IIC T4 (-20°C \leq T _a \leq +65°C) |
| | | Also to permit minor drawing changes not affect the original assessment. Testing documented in Test Report No. GB/BAS/ExTR08.0128/00 |
| Baseefa04ATEX0384 Issue 11 | 16 December 2009 | This issue of the certificate incorporates previously issued primary & supplementary certificates into one certificate and confirms the current design meets the requirements of EN 60079-0: 2006 & EN 60079-11: 2007 including the revision of the marking in accordance with these standards. |
| | | The certificate also permits: - |
| | | 1) The removal of the alternative rechargeable cell type ICP653450U and therefore the T3 variant of the equipment is now obsolete. |
| | | 2) The alternative fitting of the Hybrid 3 sub-assembly in place of the Hybrid 1A sub-assembly on the rechargeable versions of the Gasman not affecting the original assessment. |
| | | Certification Drawing No's. P5423 issue 4, P-5425-A4, 5552-CERT and 5392 were made obsolete. |
| Baseefa04ATEX0384 Issue 12 | 2 December 2011 | This issue of the certificate confirms the current design meets the requirements of EN 60079-0:2009 and adds an updated rechargeable battery drawing. The marking code remains unchanged. |
| Baseefa04ATEX0384 Issue 13 | 01 September 2014 | Confirms the current design meets the requirements of EN 60079-0:2012 and EN 60079-11:2012 and records minor changes to some drawings. The assessment is recorded in GB/BAS/ExTR14.0249/00. |



Issued 10 August 2020 Page 6 of 6

| Certificate No. | Date | Comments |
|--|-----------------------------|--|
| Baseefa04ATEX0384 Issue 14 | 04 November 2014 | Records a minor change to the Gasman Charger / Interface terminal pins not affecting the original assessment. Assessment documented in Test Report No. GB/BAS/ExTR14.0324/00. |
| Baseefa04ATEX0384 | 21 May 2018 | To permit: - |
| Issue 15 | | i) Minor component changes to the i-Modules fitted in the equipment not affecting the original assessment. |
| | | ii) Minor changes to the case materials. |
| | | iii) Minor drawing changes not affecting the original assessment. |
| | | iv) To confirm the current designs of the Gasman Oxygen or Toxic Gas Detector have been reviewed against the requirements of EN 60079-0: 2012 + A11: 2013 in respect of the differences from EN 60079-0: 2012, and none of the differences affect the equipment. |
| | | The assessment is documented in IECEx ExTR No. GB/BAS/ExTR18.0048/00 (held with IECEx BAS 05.0038 Iss. 15), Project File 16/0383. |
| Baseefa04ATEX0384 10 August 2020 Issue 16 | | This issue of the certificate permits the use of an alternative charger & Bluetooth Interface with the equipment. The Certificate Schedule on page 2 of the certificate was revised to list details of the new accessory. |
| | | The test and assessment is detailed in Certification Report No. GB/BAS/ExTR20.0114/00 (held with IECEx BAS 05.0038 Iss. 16), Project File 19/0718. |
| For drawings applicable to | each issue, see original of | that issue. |